



### Product features

All-in-one design simple but practical.

High quality die-casting aluminum structure, surface anti-aging electrostatic painting, strong corrosion resistance.

Independent convection heat dissipation, reduce the thermal resistance, improve radiation efficiency.

LED SMD3030 Cree, high optical efficiency, long lifespan.

Optical lens 70+140°, use silicone rubber.

Adjustable installation angle.

## PZL - 210

<b>POWER</b>	<b>120W</b>
<b>Luminous Efficiency</b>	<b>150LM/W</b>
<b>Total Lumen</b>	<b>18.000LM</b>
<b>Driver</b>	<b>Meanwell</b>
<b>PF</b>	<b>&gt;0.95</b>
<b>Module</b>	<b>120W</b>
<b>LED</b>	<b>LED CREE SMD3030</b>
<b>LED Qty</b>	<b>144PCS</b>
<b>CCT</b>	<b>2700K/4000K/5000K/6500K</b>
<b>CRI</b>	<b>&gt;80</b>
<b>Input Voltage</b>	<b>85-265VAC</b>
<b>Surge Protection</b>	<b>6000V</b>
<b>IP Rating</b>	<b>IP 67</b>
<b>Ra</b>	<b>≥ 80</b>
<b>Life Span</b>	<b>&gt;50.000hours</b>
<b>Install Height</b>	<b>5-7m</b>